

How To Find A Leak

Turn off the water

Before you look for leaks, make sure no water is being used inside or outside of your home. This includes all water using appliances. (i.e. water softeners, icemakers, swamp coolers, etc.)

Locate Your Water Meter

About 90 percent of all area residential water meters are located in the front sidewalk. The first step is to check your meter for movement. Look at the top of the meter. You'll notice a triangle (flow indicator) will move whenever water is passing through it. If your meter doesn't have a flow indicator, you can use the sweep hand on the register to indicate water loss. If either the flow indicator or the sweep hand is moving, you may have a leak or malfunction.

Check Your Toilets

Locating a leak is a process of elimination. Shut off one toilet at a time at the wall. In between each shutoff, go out to the water meter and check your flow indicator. If the small triangle stopped moving, that means the toilet is the culprit. If the small, red flow-indicator triangle is moving, the toilet is not the problem. Something else is causing the water flow.

Check Your Irrigation System

Shut off the anti-siphon valve that serve your sprinkler system. Check the red flow-indicator triangle at the water meter. If the flow indicator stopped moving, the sprinkler system is the problem. Check the valves and look around the yard for heavy wet areas.

Check Your Water Softener

Most water softeners have a bypass lever. Turn the lever to allow water to bypass the softener. Check the red flow-indicator triangle at the meter. If the triangle is no longer moving, you have isolated the leak to your softener. (You also can check for leaking swamp coolers, water-cooled air conditioners, ice machines and reverse osmosis units by turning the bypass lever on each and check the meter.)

Check Your Pool

First turn off the automatic fill valve and place a bucket on a step where the bucket rim is at least a few inches above the water line. Then place a heavy weight in the bucket and all water until the water level inside the bucket is equal with the water level in the pool Leave the

bucket and pool undisturbed for several hot days, then compare the water level in the bucket to the water level in the pool. If the water level in the bucket is noticeably higher than the water level in the pool. If the water level in the bucket is noticeably higher than the water level in the pool, you may be losing water to a leak. If this is the case, contact a pool leak detection specialist for further assistance.

Check Your Main Service Line

First, you need to find your water shutoff valve. This is usually in your front yard near the sewer riser cap. In your garage or near your water softener unit. Shut off the main valve, cutting off all water to your home, and go in the house and turn on a faucet to make sure the water is off. Check the red flow-indicator triangle at the meter. If the red triangle is moving, the leak is between the shutoff valve and the water meter.

If you find leak, now what?

First, close the water meter cap to prevent damage to the lens and replace the meter box lid. If you are not able to find the leak, call a professional plumber to locate and fix the leak(s). If you find a simple leak like your toilet flapper or kitchen faucet, you may want to fix the problem yourself.